

STEEL+ 1733



3 - 14 years



15 kids



40,3 m²



Material specification

- Powder galvanized and powder coated or stainless steel construction of 80 x 80 mm profile,
- Platforms, climbing walls and steps made of durable anti-slip and waterproof HPL plate,
- Roofs and side panels made of durable HDPE plate, resistant to weather conditions,
- Slides made of stainless steel with durable HDPE side panels,
- Educational panels and moving elements made of HDPE plate, resistant to weather conditions,
- Spherical windows made of polycarbonate,
- The labyrinth and frame made of weather-resistant HDPE or HPL board; the windows made of transparent polycarbonate, the ball made of plastic,
- Rudder made of durable HDPE plate, resistant to weather conditions,
- Double wall tube passage made of polypropylene,
- Durable climbing stones made of polyester resin composite with mineral fillers,
- Stainless steel bars and handrails,
- Stainless steel screws and/or screws covered with plastic caps,
- Safe end caps on top of the structure made of rubber or polypropylene,



Facilitating disability



easy access



handrails



mobility



integration



Intellectual development



manipulation



thinking



sight



Physical development



sliding



community



climbing



roofs



observation



passage



crawling





2
number of towers



2
number of slides



2
number of roofs






5
number of interactive elements



1
number of activity elements



stairs



Product technical sheet

STEEL+ 1733

Product data

Length	425 cm
Width	450 cm
Total height	313 cm
Age group	3 - 14 years
Number of users	15 kids
Safety zone	40,3 m2
Free fall height	120 cm
The height of the platforms	40, 90, 120 cm
slide platform height	90, 120 cm
In accordance with norm EN	1176-1:2017+A1:2023
Weight of the heaviest part	15,9 kg
Dimensions of the largest part	8x8x338 cm
Availability of spare parts	YES

Color options



Data is subject to change without prior notice.

Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee

30

30 year guarantee - Durability of steel and stainless steel structural elements

15

15 year guarantee - Durability of steel and stainless steel structures of mobile devices; durability of Robinia wood structural elements

10

10 year guarantee - Structural strength of HDPE, 100% recycled HDPE and HPL elements; structural elements made of 100% recycled material (composite)

5

5 year guarantee - Corrosion resistance of stainless steel and hot-dip galvanized and powder-coated steel elements, resistance to bark beetles and rotting of wooden structural elements

Detailed information in the guarantee card

Vinci Sp. z o.o.
Seminarnyja 9 Street
99-400 Łowicz

VAT: 534-265-18-84
PHONE: +48 42 203 24 99 ext. 26
M: +48 793 404 991



biuro@vinci-play.com
info@vinci-play.com
www.vinci-play.com

Surfaces according to EN 1176-1:2017+A1:2023

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		120

Product technical sheet

STEEL+ 1733

Amount of safe surface corresponding with free fall height:

HIC <60 3,4 m²

HIC 90 2,8 m²

HIC 100 7,6 m²

HIC 120 26,5 m²

Data is subject to change without prior notice.

