

# WOODEN WD1550


## **PLAYGROUND EQUIPMENT**



| Safety zone                        | 33,3 m <sup>2</sup> |
|------------------------------------|---------------------|
| Length                             | 3,86 m              |
| Width                              | 3,36 m              |
| Total height                       | 2,60 m              |
| Free fall height                   | 1,20 m              |
| Age range                          | 3-12 years          |
| In accordance EN standards         | 1176-1:2017         |
| Weight of the heaviest part [kg]   | 19                  |
| Dimension of the biggest part [cm] | 249x9x9             |
| Availability of spare parts        | Yes                 |
|                                    |                     |



### Minimal space



#### **MATERIAL SPECIFICATION**

- Construction made of the highest quality impregnated and laminated pine wood 90 x 90 mm without knots, secured from the top with polypropylene plugs
- Metal anchors made of hot dip galvanized steel, protecting the wood from direct contact with the ground to prevent rot and extending the product's life
- Platforms, climbing walls and steps made of anti-slip and waterproof plywood or HPL plates
- Side panels made of HDPE or HPL plates, resistant to weather conditions,
- Stainless steel bars and handrails, slide made of stainless steel with HDPE or HPL side panels,
- Double wall tube passage made of PP, window made of polycarbonate,
- · Calibrated stainless steel chains, preventing fingers entrapment, screws covered with plastic caps or stainless steel screws,
- Safe end caps made of polypropylene.

# ADDITIONAL COMMENTS

- equipment adapted for the disabled, intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

# **SURFACES**

Due to the free fall height of the equipment, the EN 1176-1:2017 standard allows the following surfaces: turf/ soil (A,B,C), sand with minimal layer thickness of 30 cm (A,C), synthetic material approved for free fall of 1,20 m (A,B,C).



VIA E CURIEL, 52010 Soci i (Arezzzo) e-mail: vittoria@italiangarden.it

